

## CELESTA Light Engine




Image by CrestOptics

## Bright, Stable, Turnkey 7 Laser Light Engine

Confocal • MERFISH • Super-Resolution • Optogenetics • FRAP • DNA-PAINT

With several new laser options, Lumencor's CELESTA Light Engine remains an industry leading, turnkey illuminator: designed to best support many of the highest resolution, photon-demanding, microscopy techniques in the life and material sciences. CELESTA brings together seven independent, solid-state lasers with advanced electronic control to deliver unprecedented stability, optical power and brightness. The CELESTA quattro Light Engine provides the same performance in a streamlined four or five laser format.

New in 2022 are 488 nm, 577 nm and 680 nm lasers. Now CELESTA is more configurable, with 10 laser options to satisfy your specific imaging needs. Each output is refined by a bandpass filter and merged into a common optical train, passed through a despeckler and directed to the light output port on the front panel. The light output port has a built-in adapter for facile connection to microscopes and other bioanalytical instruments through a SMA- or FC/ PC-terminated optical fiber. Output power at the distal end of the optical fiber is ~800 mW from each laser. These capabilities are assembled in an easy-to-use, compact, turnkey, device with a space-saving footprint.

CELESTA Light Engine features an advanced control system based on an onboard computer with an embedded command library. This allows facile control


using simple, intuitive commands sent to the Light Engine via USB/RS-232 or TCP serial protocols. These commands give access to basic functions of source selection, on/off switching and output intensity, as well as to an extensive panel of operating status reports and advanced control features.

Long-term stability is sustained by active power control circuitry. Linear light intensity provides robustness and reproducibility. Light output is monitored and controlled for constant photon flux over time using an internal feedback loop. A GUI hosted on the onboard computer and accessed through an ethernet connection provides convenient access to basic control functions, configuration settings and performance diagnostics.

CELESTA controls are also implemented in several commonly used image acquisition software packages. TTL trigger inputs are provided for all outputs for applications requiring fast (100 microseconds) switching time.

As with all Lumencor products, OEM customization is available upon request.

For more information on the [CELESTA Light Engine](#), please contact us at [info@lumencor.com](mailto:info@lumencor.com). To receive a purchase quotation for a CELESTA Light Engine, please submit our online [quotation request form](#).



## Features and Operating Characteristics:

Features	Details
Sources	7 Class 4 lasers (CELESTA); 4 or 5 Class 4 lasers (CELESTA quattro)
Wavelengths	405 nm, 446 nm, 477 nm, 488 nm, 518 nm, 545 nm, 577 nm, 637 nm, 680 nm, 748 nm [1]
Bandpass Filters	Integrally installed bandpass filters (one per laser line)
Output Power	~800 mW per laser line at 100% intensity [2]
Light Delivery	SMA-terminated or FC/PC-terminated optical fiber [3]
Safety Interlocks	Laser output contingent on manual (key) and remote (electronic) interlocks
Operational Control	Onboard computer with server/client architecture and embedded command library
Control Interfaces	Source selection, light output on/off and intensity via serial interface (RS-232/USB or TCP). Source selection and light output on/off via TTL
Software	Onboard GUI or PC-based image acquisition software
Optional Accessories	(1) 9-channel breakout cable for TTL triggering. (2) Critical epilluminator [4]
Power Requirements	220 W (24V DC/9.2A) power supply included
Dimensions (W x L x H)	145 mm x 340 mm x 203 mm (5.7 in x 13.4 in x 8.0 in)
Weight	9 kg /19.9 lbs
Warranty	24 months, warranty extension options available

[1] Output wavelengths  $\pm$  2 nm. [2] Custom power specifications available on customized models. [3] Optical fiber included with light engine purchase. [4] Critical epilluminator provides uniform, high-irradiance illumination for single-molecule detection applications.